

AMPLIFIED SPEAKER: IN CEILING

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA



GENERAL SPECIFICATIONS

MODEL NUMBER: AMPIC6	
POWER:	25 Watts
FREQUENCY RESPONSE:	50 Hz - 15 kHz. HF is optimized to enhance frequency response of the speaker.
THD:	<.1%
S/N:	>90 dB
INPUT CONFIGURATION:	Differential (noise reducing)
MINIMUM COMMON MODE REJECTION:	40 dB
AT LOAD IMPEDANCE:	4 Ohms (2 speakers in parallel or 4 speakers in series parallel)
MINIMUM POWER SUPPLY VOLTAGE:	8 Volts
MAXIMUM SUPPLY VOLTAGE:	14 Volts
MAXIMUM CURRENT PROTECTED:	Yes
SHORT CIRCUIT PROTECTED:	Yes
ONE WIRE TO GROUND PROTECTED:	Yes
MINIMUM LOAD IMPEDANCE:	3.2 Ohm
INPUT LOAD IMPEDANCE:	10K Ohm
MAXIMUM NUMBER OF AMPLIFIERS ON ONE LINE:	20
WARRANTY:	1 Year



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: www.owi-inc.com

E-mail: info@owi-inc.com



www.owinc.com
E-mail: info@owinc.com

