

# IN CEILING SPEAKER

6.5" 2-WAY, 8 OHMS

ARCHITECTS AND ENGINEERS  
SPECIFICATIONS / TECHNICAL DATA



## GENERAL SPECIFICATIONS

<b>MODEL NUMBER:</b>	<b>IC6 (UL Listed)</b>
<b>DESCRIPTION:</b>	6.5" 2-way in-ceiling speaker
<b>COVERED OUTDOOR:</b>	Yes
<b>IMPEDANCE:</b>	8 ohms
<b>SENSITIVITY (1W/1M):</b>	87dB 1w/M
<b>DISPERSION:</b>	140°
<b>MAX POWER:</b>	50 watts
<b>NOMINAL POWER:</b>	25 watts
<b>FREQUENCY RESPONSE:</b>	65Hz-20KHz
<b>CROSSOVER:</b>	6 dB/Octave
<b>WOOFER SIZE:</b>	6.5"
<b>WOOFER MATERIAL:</b>	Paper coated woofer with foam surround
<b>TWEETER SIZE:</b>	0.5" (13mm) balance tweeter
<b>TWEETER MATERIAL:</b>	Ferrite magnet with Mylar diaphragm material
<b>GRILL MATERIAL:</b>	Aluminum
<b>DIMENSIONS:</b>	8 3/4" (223mm) Dia. x 3 3/8" (85mm) mounting depth
<b>CUT OUT SIZE:</b>	7 11/16" (195mm)
<b>WEIGHT:</b>	2.51 lbs. (1140 gms)
<b>MOUNTING HARDWARE:</b>	Clamps - 4 each
<b>PAINTABLE:</b>	Yes



### OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: [www.owi-inc.com](http://www.owi-inc.com)

E-mail: [info@owi-inc.com](mailto:info@owi-inc.com)

