

IN CEILING SPEAKER: ALL-N-ONE

6.5" 2-WAY, 8 OHMS/70V/100 VOLTS

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA

GENERAL SPECIFICATIONS



MODEL NUMBER:	ICM6-730SET
DESCRIPTION:	6.5" 2-Way Poly Coated Woofer Swivel Tweeter
COVERED OUTDOOR:	Yes
IMPEDANCE:	8 Ohms
70 VOLT TAPS:	1.75W, 3.5W, 7W, 15W, 30W
100 VOLT TAPs:	3.5W, 7W, 15W, 30W
8 OHMS TAPs:	60W
SENSITIVITY (1W/1M):	86 dB
MAX POWER:	120 Watts
NOM. POWER:	60 Watts
FREQUENCY RESPONSE:	55 Hz - 20 kHz
CROSSOVER:	4.2 kHz
INPUT CONNECTION:	Phoenix Connector
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Poly Coated
TWEETER SIZE:	1"
TWEETER MATERIAL:	PEI
ENCLOSURE:	Built-in Metal Backcan
GRILL MATERIAL:	Aluminum
DIMENSIONS:	8" X 10" X 10"
CUT OUT SIZE:	8 3/4" Diameter
WEIGHT:	11 lbs.
MOUNTING HARDWARE:	Easy Mounting Clamps
MOUNTING BRACKET:	T-Bar (included)
PAINTABLE:	Yes
OUTDOOR RATED:	No
COVERED OUTDOOR:	Yes



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: www.owi-inc.com

E-mail: info@owi-inc.com

