

# L.A. ROCKER: LITTLE ROCK SPEAKERS

ARCHITECTS AND ENGINEERS  
SPECIFICATIONS / TECHNICAL DATA

## GENERAL SPECIFICATIONS

Enclosure: Glass Fiber Reinforced Concrete (GFRC)

Dimensions (LxWxH): 16" x 14" x 10"

Weight: 25-40 lbs. (Weight varies depending on concrete mix.)



Colors: Brown (B), Grey (G), Granite (GR), Sandstone (SS)

CURRENT MODELS/ SKU	ROCK COLORS	SPEAKER SPECIFICATIONS						
		IMPEDANCE	SYSTEM TYPE	POWER (WATTS)	FREQUENCY RESPONSE	SENSITIVITY	DISPERSION	CROSSOVER
LR703B	B=Brown	70V / 8Ω	4", 3-Way	2.5, 5, 10, 15 W	90 Hz - 20 kHz	88 dB	90°	9 kHz
LR703G	G=Grey							
LR703GR	GR=Granite							
LR703SS	SS=Sandstone			(100 Watts at 8 ohms)				
LRP6802B	B=Brown	8Ω	6", 2-Way	100 watts	70 Hz - 20 kHz	89 dB	90°	5 kHz
LRP6802G	G=Grey							
LRP6802GR	GR=Granite							
LRP6802SS	SS=Sandstone							
LRP6715B	B=Brown	70V	6", 2-Way	2.5, 5, 10, 15 W	70 Hz - 20 kHz	89 dB	90°	5 kHz
LRP6715G	G=Grey							
LRP6715GR	GR=Granite							
LRP6715SS	SS=Sandstone							
LRP6740B	B=Brown	70V	6", 2-Way	5, 10, 15, 40 W	70 Hz - 20 kHz	89 dB	90°	5 kHz
LRP6740G	G=Grey							
LRP6740GR	GR=Granite							
LRP6740SS	SS=Sandstone							

### DISCONTINUED LITTLE ROCK MODELS/SKUs AND THE RECOMMENDED REPLACEMENTS

MODEL/SKU	DESCRIPTION			RECOMMENDED REPLACEMENT - SPECS			
	IMPEDANCE	SYSTEM TYPE	MAX POWER	MODEL/SKU	IMPEDANCE	SYSTEM TYPE	MAX POWER
LR202	8Ω	4", 2-WAY	80 W	LR703	70V/8Ω	4", 3-WAY	15 W at 70V 100W at 8Ω
LR203		4", 3-WAY	100 W				
LR701	70V	4", FULL RANGE	15 W				
LR702		4", 2-WAY					
LRP502	8Ω	5", 2-WAY	120 W	LRP6802	8Ω	6", 2-WAY	100 W
LRP503		5", 3-WAY					
LRP572	70V	5", 2-WAY	15 W	LRP6715	70V	6", 2-WAY	15 W
LRP573		5", 3-WAY					
LRP5752		5", 2-WAY	50 W	LRP6740	70V	6", 2-WAY	40 W
LRP5753		5", 3-WAY					



**OWI Incorporated**  
 17141 Kingsview Avenue, Carson, CA 90746 USA  
 Tel: 310.515.1900  
 Toll Free: 800.638.1694  
 Fax: 310.515.1606  
 Web: www.owi-inc.com  
 E-mail: info@owi-inc.com

