

Venus

**DYNAMIC 360° SOUND /
180° DISPERSION**

**EASY INSTALLATION INCLUDING
HIGH CEILING APPLICATIONS**

**MORE DYNAMIC SOUND OUT
OF ONE SPEAKER**

**PERFECT FOR RETAIL STORES,
NIGHT CLUBS, SPORTS BARS,
RESTAURANTS, HOTELS, ATRIUMS,
& TRANSPORTATION CENTERS**

**FIXED OR
FREE HANGING**

AVAILABLE IN BLACK



360° of Optimum Sound

Excellence in Audio
Envirōtainment®



www.owi-inc.com

Venus

**EXTREME 360° SOUND
FROM ONE SPEAKER**



**ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA**

*Mounting Hardware:
1" EMT (far left)
or Safety Cable (right)*

MODEL NUMBER:	V-6810	V-6750	V-6715
DESCRIPTION:	6.5", Polycarbonate Woofer with Rubber Surround 4 Each 2.5" Midrange Tweeters One 1" Tweeter 4 Each Bass Ports	6.5", Polycarbonate Woofer with Rubber Surround 4 Each 2.5" Midrange Tweeters One 1" Tweeter 4 Each Bass Ports	6.5", Polycarbonate Woofer with Rubber Surround 4 Each 2.5" Midrange Tweeters One 1" Tweeter 4 Each Bass Ports
IMPEDANCE:	8 Ohms	70 Volts	70 Volts
DISPERSION:	360° x 180°	360° x 180°	360° x 180°
SENSITIVITY (1W / 1M):	89 dB	89 dB	89 dB
MAX POWER:	100 Watts	50 Watts	15 Watts
NOMINAL POWER / TAPS:	50 Watts	20, 30, 40, 50 Watts	2.5, 5, 10, 15 Watts
FREQUENCY RESPONSE:	65 Hz – 20 kHz	65 Hz – 20 kHz	65 Hz – 20 kHz
CROSSOVER:	2 kHz / 4 kHz	2 kHz / 4 kHz	2 kHz / 4 kHz
WOOFER SIZE:	6.5"	6.5"	6.5"
WOOFER MATERIAL:	Polycarbonate Rubber Surround	Polycarbonate Rubber Surround	Polycarbonate Rubber Surround
MIDRANGE TWEETER SIZE:	4 Each – 2.5"	4 Each – 2.5"	4 Each – 2.5"
MIDRANGE TWEETER MATERIAL:	Paper	Paper	Paper
TWEETER SIZE:	1"	1"	1"
TWEETER MATERIAL:	Ceramic Soft Dome	Ceramic Soft Dome	Ceramic Soft Dome
GRILL MATERIAL:	Metal	Metal	Metal
DIMENSIONS (W x H)	15" dia. x 10.5" Height	15" dia. x 10.5" Height	15" dia. x 10.5" Height
MOUNTING HARDWARE (INCLUDED):	1" dia. x 18" EMT	1" dia. x 18" EMT	1" dia. x 18" EMT
MOUNTING HARDWARE OPTION:	Safety Cable (Not Included)	Safety Cable (Not Included)	Safety Cable (Not Included)
ENCLOSURE:	Polyethylene	Polyethylene	Polyethylene
PAINTABLE:	No	No	No
COVERED OUTDOOR:	Yes	Yes	Yes
FINISHES AVAILABLE:	Black	Black	Black

INSTALLATION GUIDE ± 3dB

HEIGHT OF THE SPEAKER	8 ft.	9 ft.	10 ft.	11 ft.	12 ft.	13 ft.	14 ft.	15 ft.	16 ft.	17 ft.	18 ft.	19 ft.	20 ft.
DISTANCE BETWEEN SPEAKERS (ft.)	25	30	36	41	47	52	58	63	69	74	80	85	91
COVERAGE IN SQUARE FT. (ft ²) PER SPEAKER	491	707	1018	1320	1735	2124	2642	3117	3739	4301	5027	5675	6504

Shown: Figures for ± 3dB total variation installations.
Speaker height is measured from the tweeter to the listener's ear height of 3 ft. 6 in. from the floor.



OWI, INC.
17141 Kingsview Avenue, Carson, CA 90746 USA
tel: 310.515.1900
toll-free: 800.638.1694
fax: 310.515.1606
e-mail: info@owi-inc.com
web: www.owi-inc.com

