

L.A. ROCKER: RIVER ROCK SPEAKERS

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA

GENERAL SPECIFICATIONS

Enclosure: Glass Fiber Reinforced Concrete (GFRC)

Dimensions (LxWxH): 23" x 21" x 11"

Colors: Granite (**GR**), Sandstone (**SS**)

Weight: 30-45 lbs. (Weight varies depending on concrete mix.)

CURRENT MODELS/ SKU	ROCK COLORS	SPEAKER SPECIFICATIONS						
		IMPEDANCE	SYSTEM TYPE	MAX POWER (WATTS)	FREQUENCY RESPONSE	SENSITIVITY	DISPERSION	CROSSOVER
RIV703GR	GR=Granite	70V / 8Ω	4", 3-Way	2.5, 5, 10, 15 W (100 watts at 8 ohms)	90 Hz - 20 kHz	88 dB	90°	9 kHz
RIV703SS	SS=Sandstone							
RIVP6802GR	GR=Granite	8Ω	6", 2-Way	100 W	70 Hz - 20 kHz	89 dB	90°	5 kHz
RIVP6802SS	SS=Sandstone							
RIVP6715GR	GR=Granite	70V	6", 2-Way	2.5, 5, 10, 15 W	70 Hz - 20 kHz	89 dB	90°	5 kHz
RIVP6715SS	SS=Sandstone							
RIVP6740GR	GR=Granite	70V	6", 2-Way	5, 10, 15, 40 W	70 Hz - 20 kHz	89 dB	90°	5 kHz
RIVP6740SS	SS=Sandstone							

DISCONTINUED RIVER ROCK MODELS/SKUs AND THE RECOMMENDED REPLACEMENTS

MODEL/SKU	DESCRIPTION			RECOMMENDED REPLACEMENT - SPECS			
	IMPEDANCE	SYSTEM TYPE	MAX POWER	MODEL/SKU	IMPEDANCE	SYSTEM TYPE	MAX POWER
RIV202	8Ω	4", 2-WAY	80 W	RIV703	70V/8Ω	4", 3-WAY	15 W at 70V 100W at 8Ω
RIV203		4", 3-WAY	100 W				
RIV701	70V	4", FULL RANGE	15 W				
RIV702		4", 2-WAY					
RIVP502	8Ω	5", 2-WAY	120 W	RIVP6802	8Ω	6", 2-WAY	100 W
RIVP503		5", 3-WAY					
RIVP572	70V	5", 2-WAY	15 W	RIVP6715	70V	6", 2-WAY	15 W
RIVP573		5", 3-WAY					
RIVP5752		5", 2-WAY	50 W	RIVP6740	70V	6", 2-WAY	40 W
RIVP5753		5", 3-WAY					



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: www.owi-inc.com

E-mail: info@owi-inc.com

