



SX Series

Specifications

Wall Speaker

8 OHM 70 VOLT 100 VOLT



Description

Experience unparalleled sound quality and durability with the SX Series weatherized wall speaker, a versatile choice tailored for both residential and commercial environments. Engineered with adjustable power settings, this speaker allows for precise optimization, ensuring it operates at peak performance levels while safeguarding against potential damage. Whether enhancing the atmosphere of retail spaces, restaurants, or spas, its robust construction promises reliability and longevity in any setting. Elevate your audio experience with the SX Series, where exceptional sound meets uncompromising durability.

Specifications

Models		SX-4720	SX-5730	SX-6740
Speaker Type		Two-way Full range		
Peak power handling		120 W	160 W	240 W
Program power handling		60 W	80 W	120 W
RMS/AES power handling		30 W	40 W	60 W
Impedance		8 Ω	8 Ω	8 Ω
Incline angle	Left	36°	36°	36°
	Right	36°	36°	36°
	Bottom	88°	88°	88°
	Top	88°	88°	88°
Sensitivity (1W/1m)		84 dB	87 dB	89 dB
Sound Pressure (Max. W/1m)	@ 8 Ω	99 dB	103 dB	107 dB
	@ 100 V	97 dB	102 dB	105 dB
Frequency	Response (± 3 dB)	100 Hz - 20 kHz	85 Hz - 20 kHz	65 Hz - 20 kHz
	Range (-10 dB)	85 Hz - 20 kHz	75 Hz - 20 kHz	55 Hz - 20 kHz
Dispersion	Horizontal	120°	120°	120°
	Vertical	120°	120°	120°
Connectors		4-pin Press Terminal Block	4-pin Press Terminal Block	4-pin Press Terminal Block
Drivers		0.5" Dome tweeter	0.5" Dome tweeter	1" Dome tweeter
		4" MF / LF Woofer	5.25" MF / LF Woofer	6.5" MF / LF Woofer
Line Transformer Tappings	1	250 Ω - 100 V / Not used - 70 V / 20 W	163 Ω - 100 V / Not used - 70 V / 30 W	122.5 Ω - 100 V / Not used - 70 V / 40 W
	2	500 Ω - 100 V / Not used - 70 V / 10 W	333 Ω - 100 V / 30 W - 70 V / 15 W	250 Ω - 100 V / 40 W - 70 V / 20 W
	3	1000 Ω - 100 V / 5 W - 70 V / 2.5 W	666 Ω - 100 V / 15 W - 70 V / 7.5 W	500 Ω - 100 V / 20 W - 70 V / 10 W
	4	2000 Ω - 100 V / 5 W - 70 V / 2.5 W	1332 Ω - 100 V / 7.5 W - 70 V / 3.75 W	1000 Ω - 100 V / 10 W - 70 V / 5 W
Dimensions		140 x 200 x 135 mm (WxHxD)	175 x 250 x 155.8 mm (WxHxD)	215 x 302.9 x 189.5 mm (WxHxD)
Weight		1.246 kg	1.595 kg	2.355 kg
Operating temperature		-20°C ~ 60°C		
Front finish		Aluminium grill		
Colors		Black, White		