

# **AMP-BT2SIC5 – Two Source, 5.25” Amplified Drop Ceiling Speaker**

## **With Bluetooth Features**

Two source, 5.25”, Amplified Drop Ceiling Speakers with Bluetooth features, deliver up to 40 watts power directly to the speaker. Each powered speaker (AMP-BT2SIC5) can drive three additional speakers (IC5). One line can drive up to 10 self-amplified speakers. Lower noise feature and protection from shorts and overheating. 15Volt DC Level 5 power supply included.



### **Features:**

- Built onto the OWI IC5 In-Ceiling Speakers
- UL Listed, Energy Star, Energy Verified
- 2 Line Level Input/Sources
- Up to 40 Watts or Power – right at the speaker
- With Priority Override Feature
- Balanced Line level Output
- With Bluetooth Features
- With a 3.5 mm Jack Line Input
- 15 Volt DC power supply (UL rated-Level 5) included
- Protected from shorts and overheating
- Lower Noise Feature
- Fast and easy – install in the field
- Stereo/mono volume controls available
- Available in 1, 2 and 4 speaker packages

### **Available also in other complete install packages:**

- |                                 |  |
|---------------------------------|--|
| <a href="#">AMP-BT2SIC51</a>    | - Single speaker combination with tile bridge and backcans.                  |
| <a href="#">AMP-BT2SIC51SVC</a> | - Single speaker combination with tile bridges, backcans and volume control. |
| <a href="#">AMP-BT2SIC52</a>    | - Two speaker combination with tile bridges and backcans.                    |
| <a href="#">AMP-BT2SIC52SVC</a> | - Two speaker combination with tile bridges, backcans and volume control.    |
| <a href="#">AMP-BT2SIC54</a>    | - Four speaker combination with tile bridges and backcans                    |
| <a href="#">AMP-BT2SIC54SVC</a> | - Four speaker combination with tile bridges, backcans and volume control.   |



# **AMP-BT2SIC6 – Two Source, 6.5” Amplified Drop Ceiling Speaker**

## **With Bluetooth Features**

Two source, 6.5”, Amplified Drop Ceiling Speakers with Bluetooth features, deliver up to 40 watts power directly to the speaker. Each powered speaker (AMP-BT2SIC6) can drive three additional speakers (IC6). One line can drive up to 10 self-amplified speakers. Lower noise feature and protection from shorts and overheating. 15Volt DC Level 5 power supply included.



### **Features:**

- Built onto the OWI IC6 In-Ceiling Speakers
- UL Listed, Energy Star, Energy Verified
- 2 Line Level Input/Sources
- Up to 40 Watts or Power – right at the speaker
- With Priority Override Feature
- Balanced Line level Output
- With Bluetooth Features
- With a 3.5 mm Jack Line Input
- 15 Volt DC power supply (UL rated-Level 5) included
- Protected from shorts and overheating
- Lower Noise Feature
- Fast and easy – install in the field
- Stereo/mono volume controls available
- Available in 1, 2 and 4 speaker packages

### **Available also in other complete install packages:**

- |                                 |  |
|---------------------------------|--|
| <a href="#">AMP-BT2SIC61</a>    | - Single speaker combination with tile bridge and backcans.                  |
| <a href="#">AMP-BT2SIC61SVC</a> | - Single speaker combination with tile bridges, backcans and volume control. |
| <a href="#">AMP-BT2SIC62</a>    | - Two speaker combination with tile bridges and backcans.                    |
| <a href="#">AMP-BT2SIC62SVC</a> | - Two speaker combination with tile bridges, backcans and volume control.    |
| <a href="#">AMP-BT2SIC64</a>    | - Four speaker combination with tile bridges and backcans                    |
| <a href="#">AMP-BT2SIC64SVC</a> | - Four speaker combination with tile bridges, backcans and volume control.   |

