

AMPLIFIED SPEAKER: TRUMPET

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA



GENERAL SPECIFICATIONS

MODEL NUMBER:	AMP04TRP
POWER:	25 Watts
FREQUENCY RESPONSE:	20 Hz - 30 kHz +0-2 dB
NOISE FLOOR:	Better than 90 dB
DISTORTION:	Better than .1% at 10 Watts
INPUT:	Line Input -10 to +4 dB
INPUT CONFIGURATION:	Differential, Balanced DC Isolated
VOLUME CONTROL:	Step for Mechanical Level Memory
PROTECTION:	Short Circuit, Heat and Over Current
MAXIMUM POWER SUPPLY WIRE LENGTH:	400 Ft. with 16 Gauge Wire
MULTIPLE AMPLIFIERS:	Yes, Line Input In Parallel
EACH AMPLIFIER MAY POWER:	Four Speaker Total per Amp
INPUT/OUTPUT:	Each Amplifier has a Line Level Input and Output
CONNECTOR TYPE:	Phoenix Connector
CONDUIT ENTRY:	Two 1/2" Conduit Access Holes with Knock Outs
TYPICAL LINE LEVEL SOURCES:	CD Player, Audio Mixer, Background Music Service, Telephone PBX Dry Audio Pair Hooked to the Balanced +,- Input. There is No Shield on a Telephone Input.
HOOK UP FOR ADDITIONAL HORNS:	Wired through the Conduit Entry, Use the 4 Way Binding Posts for Additional High Level Speakers Hooked up to the Amplifier.
FOR FOUR HORNS:	Wire them Series Parallel to Achieve a 4 Ohm Load Impedance
POWER SUPPLY:	12 Volts
COLOR:	White



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: www.owi-inc.com

E-mail: info@owi-inc.com

