


IR20REC-KIT


INFRARED WIRELESS MICROPHONE SYSTEM

INSTALLATION INSTRUCTIONS



owi[®]
OWI Incorporated
Established 1978

This package contains the ff:



1 each IR20REC-CASE – WIRELESS MIC RECEIVER



2 each CRS-IRS - IR SENSORS



1 each CRS-PMIC - PENDANT MICROPHONE



1 each CRS-PENCH - PENDANT CHARGER



1 each CRS-PBAT3.7 - PENDANT MICROPHONE BATTERY



1 each CRS-LMIC - LAPEL MICROPHONE



1 each PS15VDC35AL5 – POWER SUPPLY



2 each CABINET KEYS

Optional Accessories (Sold Separately)


1 each CRS-HSMIC - HEADSET MICROPHONE

1 each CRS-HHMIC - HANDHELD MICROPHONE

1 each CRS-HHBAT2.4 - HANDHELD MICROPHONE BATTERY

1 each CRS-HHMCs - HANDHELD MICROPHONE CHARGER

SAFETY INSTRUCTIONS



**CAUTION: TO REDUCE THE RISK OF ELECTRIC SHOCK,
DO NOT REMOVE COVER (OR BACK)
NO USER-SERVICEABLE PARTS INSIDE
REFER SERVICING TO QUALIFIED SERVICE PERSONNEL**



The lightning flash with arrowhead symbol, within an equilateral triangle, is intended to alert the user to the presence of un-insulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.



The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

**WARNING: TO REDUCE THE RISK OF FIRE OR ELECTRIC
SHOCK, DO NOT EXPOSE THIS APPLIANCE
TO RAIN OR MOISTURE**



**WARNING
MOVE WITH CARE**

Read all of these instructions before operating and save instructions for later use.

1. **Read Instructions** – All the safety and operating instructions should be read before the appliance is operated.
2. **Retain Instructions** – The safety and operating instructions should be retained for future reference.
3. **Heed Warnings** – All warnings on the appliance and in the instructions should be adhered to.
4. **Follow Instructions** – All operating and use instructions should be followed.
5. **Water and Moisture** – The appliance should not be used near water – for example, near a bathtub, washbowl, kitchen sink, laundry tub, in a wet basement or near a swimming pool.
6. **Carts and Stands** – The appliance should be used only with a cart or stand that is recommended by the manufacturer. An appliance and cart combination should be moved with care. Quick stops, excessive force, and uneven surfaces may cause the appliance and cart combination to overturn.
7. **Wall or Ceiling Mounting** – The appliance should be mounted to a wall or ceiling only as recommended by the manufacturer.
8. **Ventilation** – The appliance should be situated so that its location or position does not interfere with its proper ventilation. For example, the appliance should not be situated on a bed, sofa, rug, or similar surface that may block the ventilation openings; or, placed in a built-in installation, such as a bookcase or cabinet that may impede the flow of air through the ventilation openings.
9. **Heat** – The appliance should be situated away from heat sources such as radiators, heat registers, stoves, or other appliances (including amplifiers) that produce heat.
10. **Power Sources** – The appliance should be connected to a power supply only of the type described in the operating instructions or as marked on the appliance.
11. **Grounding or Polarization** – Precautions should be taken so that the grounding or polarization means of an appliance is not defeated.
12. **Power-Cord Protection** – Power-supply cords should be routed so that they are not likely to be walked on or pinched by items placed upon or against them, paying particular attention to cords at plugs, convenience receptacles, and at the point where they exit from the appliance.
13. **Cleaning** – The appliance should be cleaned only as recommended by the manufacturer.
14. **Power Lines** – An outdoor antenna should be located away from the power lines.
15. **Nonuse Periods** – The power cord of the appliance should be unplugged from the outlet when left unused for a long period of time.
16. **Object and Liquid Entry** – Care should be taken so that objects do not fall and liquids are not spilled into the enclosure through openings.
17. **Damage Requiring Service** – The appliance should be serviced by qualified service personnel when:
 - A. The power-supply cord or the plug has been damaged; or
 - B. Objects have fallen, or liquid has spilled into the appliance; or
 - C. The appliance has been exposed to rain; or
 - D. The appliance does not appear to operate normally or exhibits a marked change in performance; or
 - E. The appliance has been dropped or the enclosure damaged.
18. **Servicing** – The user should not attempt to service the appliance beyond that described in the operating instructions. All other servicing should be referred to qualified service personnel.

INTRODUCTION

Congratulations and thank you for purchasing the OWI IR20REC-KIT Infrared Wireless Microphone System. This compact system is suitable for Classrooms, Training rooms, Conference rooms and for Public speaking.

The OWI IR20REC-KIT is an Infrared (IR) Wireless Mic system that allows the speaker the freedom to move about the room without the restriction of a microphone cable. The two included CRS-IRS IR Sensors allow use of several options of microphones.

The IR20REC-KIT is a receiver that provides inputs for infrared wireless microphones. The system outputs the same mono signal to up to two speakers).

The CRS-PMIC is a combination IR Wireless PENDANT MICROPHONE AND BATTERY CHARGER. It gets clipped onto a coat or shirt pocket, or hung around the presenter's neck on a lanyard and is then used as a wireless microphone allowing for a hands free presentation.

The CRS-PMIC also features a MIC Input that connects to either of the also included CRS-LMIC LAPEL MICROPHONE or optional CRS-HSMIC HEADSET MICROPHONE. These two ultra-sensitive mics provide additional options for hands-free presentations.

The CRS-HHMIC Wireless Microphone (optional) is a HAND-HELD IR WIRELESS MICROPHONE. This option can be used by the speaker for presentation or can be passed around the classroom or audience to allow questions to be clearly heard by all.

The IR Wireless Microphones are similar to 'normal' mics in how they detect speech, but rather than directly connecting to a PA or other amplifier, they convert the audio signals into very strong IR pulses (invisible light pulses) that are 'seen' by the IR Sensors. The Sensors receive these pulses and output electrical pulses to the IR20REC-KIT, where the electrical pulses are converted back to audio signals, amplified and output to the speakers.

IR is invisible light and IR systems typically require a direct line-of-sight from the transmitter (microphone) to the receiver (IR Sensors) to operate. The IR20REC-KIT was designed with ultra-high output IR circuitry that allows the IR pulses output from the microphones to reflect off ceiling, wall and hard floor surfaces. The IR Sensors are designed to 'see' IR from any direction, allowing uninterrupted presentations.

The IR20REC-KIT is easy to install and operate. Once set up, it will be ready for class every day. One important point: Just as students need sleep to re-charge, the microphone batteries need to be kept at peak performance levels as well, so it is important to re-charge the batteries before each use.

When not in use, the IR20REC-KIT provides a secure, locking storage space for the Pendant, Lapel and Headset Microphones, so they will never get misplaced.

The IR20REC-KIT when combined with OWI's MC4 and Amplified in-ceiling speakers help create professional easy to hear presentations of both spoken content and audio.

OWI IR20REC-KIT Infrared Wireless Microphone System. Always at the head of the class.

IR20REC-CASE FEATURES



Figure 1. IR20REC-CASE Top View - Door Closed

IR20REC CABINET FEATURES

1. **DOOR LOCK** – Locks the **IR20REC-CASE Door** to keep unauthorized fingers off the system controls and settings. Also allows safe storage of the **Pendant**, **Headset** and **Lapel Microphones**.




Figure 2. IR20REC-CASE Bottom View

2. **MOUNTING KEYHOLES** – Two screw keyholes for securing the **IR20REC-CASE** to a wall or shelf.




Figure 3. IR20REC-CASE Front Panel

IR20REC-CASE FRONT PANEL FEATURES

The IR20REC-CASE Front Panel features all of the controls for the IR20REC-KIT System.

3. **POWER SWITCH** – One, two position toggle switch turns the power mains to the **IR20REC-CASE ON/OFF**.
4. **STORAGE SPACE** – Internal compartment allows safe storage of the **Pendant, Headset and Lapel Microphones**.
5. **WIRE ACCESS** – Space in the **IR20REC-CASE** cabinet allows connection to two wired microphones, with the door closed. The power supply wire goes thru this slot also.
6. **VOLUME CONTROL** – One, rotary potentiometer sets the volume output of the **Microphone Inputs** to the **Speakers**.
7. **BALANCED OUTPUT TERMINAL** – Phoenix connector
8. **POWER SUPPLY INPUT** – 15 volts DC, 3.5 amps




Figure 4. IR20REC-CASE Inside Panel

IR20REC-CASE INSIDE PANEL FEATURES

A Volume Control is inside the panel.

9. **DOOR LOCK SLOT** – Opening in the IR20REC-CASE chassis secures the lock blade when door is locked.




Figure 5. IR20REC-CASE Top Side Panel

IR20REC-CASE TOP SIDE PANEL FEATURES

The IR Sensors get connected to the Top Panel

10. **IR SENSOR JACKS** – Three, 3.5mm mini jacks connect to the **CRS-IRS IR Sensors** for input of IR pulses (audio signals) from the **Headset, Lapel, Pendant or Handheld Microphones**. Use any two of the three inputs with the included IR Sensors.




Figure 6. IR20REC-CASE Bottom Panel

IR20REC-CASE BOTTOM SIDE




Figure 7. CRS-IRS IR Sensor

CRS-IRS IR SENSOR FEATURES

11. **MINI PLUG** – One, 3.5mm mini plug connects to one of the three **IR Sensor Jacks** on the **IR20REC-CASE Side Panel**.
12. **CABLE** – 50' cable allows the **IR Sensors** to be positioned away from the **IR20REC-CASE** for optimum coverage for reception of IR pulses from the **CRS IR Microphones**.
13. **ON LED** – One, LED illuminates green to indicate that the **CRS System** is ON and the **IR Sensors** are connected and active.
14. **IR SENSOR** – Senses the IR pulses output from the **CRS IR Microphones**. Must be positioned to have clear 'line-of-sight' to the classroom and any location that the **CRS Microphones** may be used. The **IR Sensor** senses IR in an omni-directional pattern (140° off-axis) and will also sense IR reflected off the ceiling, wall and hard floor surfaces. It has a range of 66 feet.



Figure 8. CRS-HHMIC Hand Held Microphone (Optional)

CRS-HHMIC HAND HELD MICROPHONE FEATURES (Optional)

The HHMIC Hand Held Microphone is an optional accessory that can be used for presentations or can be passed around the room for Q&A so everyone in the room can clearly hear questions from the class or audience.

NOTE 1: The **CRS-HHMIC** is an optional accessory and must be purchased separate from the **IR20REC-KIT**.

NOTE 2: The **CRS-HHMCS Charger** is also an optional accessory and is purchased separate from *both* the **IR20REC-KIT** and **CRS-HHMIC**.

15. ON LED – One LED illuminates green to indicate that the **microphone** is ON.

16. ON/OFF SWITCH – Turns the **microphone** ON/OFF.

17. IR OUTPUT ARRAY – High output IR LED's output audio as infrared pulses in an omni-directional pattern that are received by the **CRS-IRS IR Sensors**. The **IR Sensors** output electrical DC pulses to the **IR20REC-CASE** which converts them back to audio signals, amplifies them and outputs the audio to the **Speakers**.

18. CHARGER CONTACTS – These contacts charge the microphone's re-chargeable battery when inserted into the **CRS-HHMCS Hand Held Microphone Charger**.

NOTE: The **CRS-HHMCS Charger** is also an optional accessory and is purchased separate from *both* the **IR20REC-KIT** and **CRS-HHMIC**.




Figure 9. CRS-PMIC Pendant Mic/Charger

CRS-PMIC PENDANT MIC/CHARGER FEATURES

The CRS-PMIC Pendant Microphone can be used as a wireless microphone itself or as an IR Transmitter when used with the Lapel or Headset Mics.

19. **MIC INPUT** – One, 3.5mm mini jack connects to the mini plug on either the **CRS Lapel Mic** or **Headset Mic**. When either is connected to this jack, it overrides the **Pendant Microphone**, so only the **Lapel Mic** or **Headset Mic** will be active.
 20. **CLIP** – Clips the **Pendant Mic** on to the included **lanyard** or a coat or shirt pocket for use as a hands free microphone.
 21. **BATTERY DOOR** – Removable battery door for access to the AA re-chargeable Lithium battery. A regular alkaline battery can be used if necessary, but will not last as long as the Lithium (approx. 4 hours).
- NOTE: THE PENDANT IS ALSO A CHARGER. DO NOT CONNECT THE CHARGER POWER SUPPLY WHEN USING NON-RECHARGEABLE BATTERIES!**
22. **IR OUTPUT ARRAY** – High output IR LED's output audio as infrared pulses in an omni-directional pattern that are received by the **CRS-IRS IR Sensors**. The **IR Sensors** output electrical DC pulses to the **IR20REC-CASE** which converts them back to audio signals, amplifies them and outputs the audio to the **Speakers**.
 23. **MICROPHONE** – The **Pendant Microphone** is located at the top of the Pendant.
 24. **ON LED** – One LED illuminates green to indicate that the microphone is ON.
 25. **ON/OFF SWITCH** – Turns the **Pendant** ON/OFF.
 26. **6V DC IN** – One 3.5mm mini jack connects to the included **CRS-PENCH Charger Power Supply** for re-charging the Lithium battery. (Charging Time: 3 Hours).
- NOTE: THE PENDANT IS ALSO A CHARGER. DO NOT CONNECT THE CHARGER POWER SUPPLY WHEN USING NON-RECHARGEABLE BATTERIES!**



Figure 10. CRS-LMIC Lapel Mic

CRS-LMIC LAPEL MIC FEATURES

The CRS-LMIC Lapel Microphone is used with the Pendant Mic for inconspicuous hands-free presentations.

27. MICROPHONE – Detects audible sound such as voice. Should be positioned as close to the speaker's mouth as possible.

28. LAPEL CLIP – Attaches the **Lapel Microphone** to a jacket lapel, shirt or blouse.

29. MINI PLUG - Connects to the **MIC Input** on the **CRS-PMIC Pendant**. High output IR LED's on the Pendant output audio as infrared pulses in an omni-directional pattern that are received by the **CRS-IRS IR Sensors**. The IR Sensors electrical DC pulses to the **IR20REC-CASE** which converts them back to audio signals, amplifies them and outputs the audio to the **Speakers**.

NOTE: When connected, the **Lapel Mic** overrides the **Pendant Microphone**, so only the **Lapel Mic** will be active.




Figure 11. CRS-HSMIC Headset Mic (Optional)

CRS-HSMIC HEADSET MIC FEATURES (Optional)

The CRS-HSMIC Lapel Microphone is used with the Pendant Mic and is another option for hands-free presentations.

NOTE: The **CRS-HSMIC** is an optional accessory and must be purchased separate from the **IR20REC-KIT**.

30. **MICROPHONE** – Detects audible sound such as voice. Should be positioned as close to the speaker's mouth as possible.
 31. **MIC BOOM** – Adjustable mic boom allows the microphone to be set to the optimum position. The **Boom** will extend out from the **Headset** by carefully pulling the **Boom**, *not the microphone*, from the **Boom Hinge**. The **Boom** can also be swiveled into position by carefully turning the **Boom** at the **Boom Hinge**. Push the **Wire Clips** *toward the Boom Hinge* to create slack in the wire *before* adjusting. Try not to flex or strain the wire connection at the end of the boom more than necessary to avoid damaging the wire.
 32. **BOOM HINGE** – Allows positioning the **microphone** as described in **Item 38** above.
 33. **EAR CLIPS** – Secures the **Headset** by wrapping the ear clips around the user's ears.
 34. **WIRE CLIPS** – Secure the **Headset Wires** to the **Headset**.
 35. **MINI PLUG** – Connects to the **MIC Input** on the **CRS-PMIC Pendant**. High output IR LED's on the **Pendant** output audio as infrared pulses in an omni-directional pattern that are received by the **CRS-IRS IR Sensors**. The IR Sensors output DC electrical pulses to the **IR20REC-CASE** which converts them back to audio signals, amplifies them and outputs the audio to the **Speakers**.
- NOTE:** When connected the **Headset Mic** overrides the **Pendant Microphone**, so only the **Headset Mic** will be active.




Figure 12. Typical Classroom Application

INSTALLATION

IR20REC-CASE

The IR20REC-CASE can be wall, ceiling or shelf mounted. It should be located in a central location that allows the **IR Sensors** to be equally spread in the classroom for optimum visibility to the **microphones**. It should be installed in a location free from moisture or humidity. The location should also be easily accessible for operation.

Wall Mount

The **IR20REC-CASE** has two screw keyholes on the **Bottom Panel** that allow it to be secured to a wall or cabinet. (**Figure 2**) Whenever possible, the screws for the keyholes should be secured to a wood panel instead of drywall to avoid having the screws work loose over time after repeated use of the **IR20REC-KIT**. If use of a wood panel is not possible or desirable, use **screw anchors** to secure the mounting screws to the drywall. There is an additional, smaller screw hole in the **IR20REC-CASE Storage Space** that can also be used for added stability. Leave enough space above the unit (3" minimum) for **IR Sensor** connections.

1. Using two **1x6 Drywall Screws**, or similar, space the screws 12 1/8" apart, on a level line.
2. Tighten the screws until they protrude just over 1/16" (the thickness of the metal cabinet) from the wall surface.
3. Position the **IR20REC-CASE** so the wide opening of the **keyholes** aligns with the **screw heads**.
4. Push the **IR20REC-CASE** toward the wall surface and then carefully pull it down until the screws 'lock' into the narrow gap of the keyholes. Be careful to not pull the screws out of the wall.
5. Secure the **IR20REC-CASE** with a third screw through the **hole** in the **Storage Space**.




Figure 13. IR Sensor Wall Mount Adaptor

CRS-IRS IR SENSORS

The **CRS Microphones** output **IR Pulses** that are invisible light pulses. Ideally, the **IR Sensors** should be 'line-of-sight' to the **microphones**. The microphones output very strong IR pulses that will reflect off wall, ceiling and hard floor surfaces and are then 'seen' by the sensors which enhances system performance when a microphone is moving around a classroom. The IR Sensors should be installed on wall surfaces as high up the wall as possible (in a normal ceiling room) and one should be installed on *each side* of the room for best coverage.

1. Attach the **Wall-Mount Adaptor** to the **CRS-IRS** as shown in **Figure 13**.
2. Mount the **CRS-IRS** as high on the wall as possible, but at least seven feet, so people walking past or standing in front of the sensor will not block the line-of-sight to the microphones.
3. Pull **CRS-IRS Wire** to **IR20REC-CASE** location.




Figure 14. Typical CRS System Connections

CONNECTIONS

The IR20REC-KIT System requires only a few simple connections and sets up in minutes. The only required connections are the **IR Sensors** and **Speakers**.

IR Sensors

1. Connect the **CRS-IRS IR Sensor mini plugs** to any two of the three **IR Sensor Inputs** on the **IR20REC-CASE Side Panel**.

Balanced Output

1. Strip approximately $\frac{1}{4}$ " off each lead and twist the ends so there are no loose strands that can cause shorts. The recommended wire size is 14 to 16 gauge.
2. Connect to the appropriate +, - and S (Shield) Terminal. Maintain polarity.

NOTE: The **IR20REC-KIT** has balanced mono output.




Figure 15. IR20REC-KIT System Signal Path

OPERATION

1. IF TURNING THE SYSTEM ON FOR THE FIRST TIME, turn the **VOL Knob** all the way down (full counterclockwise).
2. With all system connections confirmed, press the **Power Switch** to turn the system **ON**.
3. If using the **Lapel** or **Headset Mic**, connect to the **Pendant** as shown in **Figure 16**. Be sure the **Pendant** is pointing toward the **IR Sensors** so the **IR Pulses** from the **Pendant** will be 'seen' by the **IR Sensors**.
4. Turn the **Hand Held Microphone** (or **Pendant**) **ON**.
5. Set the **VOL Knob** on the **IR20REC-CASE** to **12 o'clock**.
6. Adjust the **VOLUME KNOBS** as appropriate so the **microphone(s)** can be clearly heard throughout the entire room. (Set to the highest comfortable listening level to avoid listener fatigue.)
7. When finished using the system, turn the **microphones OFF** and turn the **IR20REC-CASE POWER Switch OFF**. Do not change the Volume settings. They will now be set for typical use in that room and should not need further adjustment.

BATTERIES

Be sure to charge the batteries before each use.

Hand Held Microphone recharge time: approximately 4 hours.

Pendant recharge time: approximately 3 hours.




Figure 16. Using the Lapel Mic and Pendant

POWER SUPPLY


PS15VDC35AL5	SPECIFICATIONS
Input	100 to 240 VAC, 50-60 Hz, 1.4A Note: Be sure to use the correct polarity on the power input.
Output	15 VDC, 3.5 amperes
Wire gauge and length	Minimum 18 gauge up to 40 feet maximum length
Electrical, Power Supply	UL Listed, Level 5 (Energy Star)
Weight	0.45 pounds
Size	4.7"H x 2"W x 1.2"D

CAUTION: The Power Supply is not to be used in air handling spaces.

**Note: Maximum power requires the replacement of the 15 volt supply with a 22 volt supply and Energy Star and UL approvals no longer apply.*

Power Supply Wire Gauge and Length - Minimum 18 gauge up to 40 feet maximum length

PS15VDC35AL5 Grounding Illustration



SPECIFICATIONS

IR20REC-CASE RECEIVER

IR Carrier Frequency	2.06MHz and 2.56MHz
Deviation Range	± 40kHz
Signal to Noise WIRELESS MIC	≥100dB
THD	<0.5% @ 1KHz
Frequency Response	60Hz-14KHz ±3dB
Output Power	2-30W (Max)
Voltage	110V AC / 60Hz
Power Consumption (max)	70W
Dimensions	14.7W x 8.1H x 2.6D inches (372.2 x 204.2 x 65.5mm)
Weight	4.74lbs (2.15kg)
Color	White

CRS-IRS IR SENSORS

Carrier Frequency	2.06MHz or 2.56MHz
Off Axis Performance	140°
Range	66 feet (20mm)
Dimensions	3.25W x 2H x 1.25D inches (82.55 x 50.8 x 31.75mm)

CRS-PMIC PENDANT MICROPHONE

Polar Pattern	Unidirectional Electret Condenser Microphone
IR Carrier Frequency	2.06MHz or 2.56MHz
Battery	3.7V 800MAh AA Lithium
Dimensions H x W x D	4.7 x 1.3 x 0.7 inches (120 x 34 x 18 mm)
Weight (with battery)	0.13lbs (.57kg)

CRS-PENCH PENDANT CHARGER

Input Voltage	110V AC / 60Hz
Output Voltage	6V DC
Output Current	1000mA

CRS-LMIC LAPEL MICROPHONE

Pattern	Cardioid Directional
Frequency Response	55Hz-17KHz ± 2dB
Sensitivity	47 dB ± 2dB (1KHz, 0dB = 1v/Pa)
Output Impedance	2.2kΩ
Signal To Noise	60dB
Power	5V DC
Power Consumption	0.5mA (Max)
Cable Length	40 inches (1.016m)
Accessory	Windscreen

CRS-HSMIC HEADSET MICROPHONE

Element	Permanently Polarized Condenser
Pattern	Cardioid
Frequency Response	100Hz-17KHz
Sensitivity	-44dB (6.3mV) 1V @1 Pa
Max Input Sound Level	120dB 1KHz @1% THD
Signal To Noise	60dB 1KHZ @ 1 Pa

Battery Current/Life	0.1mA @ 5V
Voltage	2.5-11V DC
Cable Length	40 inches (1.016m)
Weight	0.04 lbs (0.02kg)
Dimensions	
Headset	6.1 inches (155 mm)
Microphone	0.20 inches (5.1 mm)
Body	6.7 inches (170 mm)
Accessory	HM-008 Windscreen

CRS-HHMIC HANDHELD MICROPHONE

Polar Pattern	Uni-directional Dynamic
Carrier Frequency	2.06MHz and 2.56MHz
Battery	2.4V NiMH 2400MAh approx 7 hours (low output); 4 Hours (high output)
Dimensions	1.9 x 9.5 inches (50 x 240mm)
Weight (with Battery)	.6lbs (.25kg)
Color	Black

CRS-HHMCS HANDHELD MICROPHONE CHARGER

Charge Mode	Pulsed Fast Charge
Power	110V AC / 60Hz
Charging Power	3.8V DC @ 400mA x 2
Charge Time	3 hours
Dimensions	5.71W x 2.6D x 4.13H inches (145 x 65 x 105mm)
Color	Black



**17141 Kingsview Avenue
Carson, CA 90746-1207
Telephone: 310.515.1900
Fax: 310.515.1606
Web: www.owi-inc.com**

02/07/17