

NEW

Model: ICM8

8" IN-CEILING SPEAKER

CHOOSE SUBWOOFER, HIGH CEILING
OR FULL RANGE – WITH A SWITCH



① Full Range

② High Ceiling

③ Subwoofer



Switch for:

- ① Full Range
- ② High Ceiling
- ③ Subwoofer



Tap Selector

- 25/70/100 Volts or 8 Ω
- 100 Watts at 8 Ω
100 Watts at 70/100 Volts

Includes:

- Speaker
- Transformer
- Steel Backcan
- Grill
- T-Bar Bracket

- Easy Install



OWI-INC.COM
/icm8

ANOTHER OWI INNOVATION!



OWI®
OWI Incorporated
Established 1978

NEW **Model: ICM8**

8" IN-CEILING SPEAKER

CHOOSE SUBWOOFER, HIGH CEILING
OR FULL RANGE – WITH A SWITCH



① Full Range

② High Ceiling

③ Subwoofer

GENERAL SPECIFICATIONS

Model Number:	ICM8
Description:	Full Range, 8" In-Ceiling 25V/70V/100V, 100W Switchable Full Range/High Ceiling/ SUB
Impedance:	8 Ω or 25 V / 70 V / 100 V
25 Volt Taps:	13 W, 6.3 W, 3.1 W, & 1.6 W
70 Volt Taps:	100 W, 50 W, 25 W, & 13 W
100 Volt Taps:	100 W, 50 W, & 25 W
8 Ω Tap:	Yes
Sensitivity (1W/1M):	91 dB
Max Power:	200 W
Nominal Power:	100 W
Frequency Response:	80 Hz ~ 17 kHz (-3 dB) / 55 Hz ~ 20 kHz (-10 dB)
Crossover:	Full Range (1.8 kHz) / 125 Hz / 5 kHz
Dispersion (Coverage):	112°
Input Connection:	Removable locking connector with screw-down terminals. 2 input terminals and 2 loop-thru output terminals. Max. wire 12 AWG (2.5 mm ²)
Woofer Size:	8" Diameter
Woofer Material:	Paper Cone-Coated
Tweeter Size:	1" Diameter
Tweeter Material:	Silk Dome Tweeter
Grill Material:	Aluminum
Dimensions (HxWxD):	11" x 13" x 13"
Cut Out Size:	11 3/4"
Mounting Hardware:	Yes
Mounting Bracket (Included):	Yes
Weight:	17 Lbs.
Paintable:	Yes
Outdoor Rated:	No
Outdoor - Covered:	Yes
Master Carton Dimensions:	30 3/4" x 16" x 14 3/4"

